




DECLARATION OF PERFORMANCE
No. 535106

1. Unique identification code of the product-type: **Tec7**
2. Intended use/es:
Sealant for façade, exterior and interior, in Cold Climate (F EXT-INT CC 12.5 E)
Sealant for sanitary joints (S XS1)
Sealant for pedestrian walkways, exterior and interior, in Cold Climate (PW EXT-INT CC 12.5 E)
3. Manufacturer: **Novatech International NV**
Industrielaan 5b
2250 Olen - Belgium
4. System/s of AVCP: **3 plus 3**
5. Harmonised standard: **EN 15651-1: 2012-12**
EN 15651-3: 2012-12
EN 15651-4: 2012-12
6. Notified body: **NB 0757 - IFT Rosenheim**





7. Declared Performance(s)

Conditioning: Method B

Substrate: anodized aluminum (with PPE primer), concrete M1 (with SIP 1K primer)

| Essential Characteristics | Performance | Harmonized Technical Specification |
|--|-------------|---|
| Reaction to fire | Class E | EN 15651-1: 2012-12 EN 15651-3: 2012-12 EN 15651-4: 2012-12 |
| Release of chemicals dangerous to the environment and health | NPD | |
| Water tightness and air tightness | | |
| Resistance to flow | ≤3mm | |
| Loss of volume | ≤10% | |
| Tensile properties at maintained extension after water immersion | NF | |
| Tensile properties at maintained extension | NF | |
| Tensile properties at maintained extension at -30°C | NF | |
| Adhesion/cohesion properties at maintained extension after water immersion | NF | |
| Adhesion/cohesion properties at maintained extension after saltwater immersion | NF | |
| Microbiological growth | 0 | |
| Tear resistance | NF | |
| Durability | NF | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Dr. Gunther Dreezen

Director of R&D
Olen, 18 March 2025

